

# SPIROVENT & SPIROVENT SOLAR - AUTOCLOSE

Microbubble Deerator | Mikroluftblasenabscheider | Microbellen afscheider | Séparateur de microbulles | Disareatore di microbolle | Desaireador de microburbujas



Mounting and operating instruction | Montage- und Betriebsanleitung | Montage en bedieningsinstructies | Installation et mode d'emploi | Operazioni di montaggio e uso | Instrucciones de montaje y operación

For article numbers | Für Artikelnummer | Voor artikelnummers | Pour les articles | Per articolo numero | Para los artículos

UA022W, UA028W, UA075W, UA100W, UA125W, UA150W, UA200W, UA022WFBA08, UA028WFBA08, UA075WFBA08, UA100WFBA08, UA125WFBA08, UA150WFBA08

76.153\_00



Acc.PED (2014/68/EU §4.3)

0-... bar  
0-... °C

UA022W, UA028W, UA075W, UA100W  
UA022WFBA08, UA028WFBA08  
UA075WFBA08, UA100WFBA08

UA125W, UA150W, UA200W,  
UA125WFBA08, UA150WFBA08

1

H<sub>2</sub>O

UA...W ≤ 50% glycol  
UA...WFBA08 20% < glycol < 50%

UA022W - UA200W

2

68 mm

32 mm  
2 mm

15 mm  
15 mm

22 mm  
28 mm

1 2 3 4 5

3

Rp 3/4  
Rp 1  
Rp 1 1/4  
Rp 1 1/2  
Rp 2

max. 40 Nm

4 5

6

Test

0 bar  
Pmax = 1,5 x ...  
0 bar

7